

Data you can rely on. People you can trust.

Vitalograph micro

Low cost spirometry made simple

Reliable, affordable spirometry testing is easier than ever with the new Vitalograph micro[™]. This compact, lightweight, handheld spirometer is not only great value but it is packed with a host of features including full colour touch screen, icon driven menu and highly accurate and robust flow sensor technology.


- Supplied with Vitalograph Reports Software
- > Configurable PDF reports for archiving or printing
- Full colour touch screen
- > Clear sounds for audio feedback
- Real-time test quality prompts
- > Flow/Volume and Volume/Time curves in real time
- > Expandable graph views for full visualisation
- Display overlay of 3 best blows, best test and LLN
- Simple icon driven menu for ease of use
- Choice of over 40 parameters
- > Pre and post bronchodilator testing options
- Predicted sets including ERS, NHANES & GLI
- > Removable flowhead for easy cleaning


Benefits of Fleisch technology

The micro features a Fleisch Pneumotachograph. This diagnostic flow measurement technology offers a wide range of advantages

- Highly accurate and reliable in the measurement of very low flows and very high flows
- Robust and durable
- Accurate, linear and stable
- Simple to use, decontaminate and maintain









Technical specification:

Product: Vitalograph micro

Model Number: 6300

Net Size: 83mm x 91mm x 32mm

Net Weight: 0.25 kg

Flow Detection Principle: Fleisch type pneumotachograph

Volume Accuracy: better than ±3% (or 0.05L) Max. volume 9.99L, Min. volume 0.01L

Flow Accuracy when Operated in Operating Temperature Range Conditions: $Flow \pm 10\%$, Max. flow rate ± 16 L/s, Min. flow rate ± 0.02 L/s

Recommended Operating Temperature Range: 17– 37°C (ISO26782 limits), Design limits 10 – 40°C

Storage Temperature: 0 – 50°C

Storage Relative Humidity: 10% – 95%

Performance Standards: EN ISO 23747:2009 & ISO 26782:2009 & ATS/ERS 2005

Battery Type: 4 x 1.5 AAA alkaline non-rechargeable **Power Supply:** 5V USB power supplied by mini USB cable

Safety Standards: EN 60601 (IEC 60601)

Medical Safety Standard: Medical Devices Directive 2007/47/EC

Designed and Manufactured Under: ISO 13485:2003, FDA 21 CFR 820, CMDR SOR 98/282 and JPAL

Communications: USB

User Interface: Touchscreen colour LCD, power button

Volume Detection: Flow integration

sampling @100Hz

Maximum Test Duration: 90 seconds

Maximum Displayed Volume: 10L

Linearity: Better than ±3%

Power: 5 Watts

Printer: Use Vitalograph Reports to print to pdf

Ordering info:

63310 6300 Vitalograph micro
20242 2024 SafeTway® Mouthpieces (200)
2030 Noseclips Disposable (200)
28350 2820 BVF™ Bacterial/Viral Filters (50)
36020 2040 Precision Syringe 3-L

Vitalograph is a world leading provider of outstanding quality cardio-respiratory diagnostic devices, clinical trial services and medical equipment servicing. With a pioneering heritage of excellence spanning half a century Vitalograph continues to make valuable contributions to effective medical care and enhanced quality of life.



Your cardio-respiratory partner

Vitalograph Ltd, UK Maids Moreton, Buckingham MK18 1SW England Tel: (01280) 827110 Fax: (01280) 823302 E-mail: sales@vitalograph.co.uk www.vitalograph.co.uk

Vitalograph Inc 13310 West 99th Street Lenexa, Kansas, 66215 USA Toll Free: 800 255 6626 Tel: (913) 730 3200 Fax: (913) 730 3232 E-mail: vitcs@vitalograph.com www.vitalograph.com Vitalograph Ltd, International Maids Moreton, Buckingham MK18 1SW England Tel: +44 1280 827120 Fax: +44 1280 823302 E-mail: sales@vitalograph.co.uk www.vitalograph.eu

Vitalograph (Ireland) Ltd Gort Road Business Park Ennis, Co Clare Ireland Tel: +353 65 6864100 Fax: +353 65 6829289 E-mail: sales@vitalograph.ie www.vitalograph.ie Vitalograph GmbH Rellinger Straße 64a D-20257 Hamburg Germany Tel: +49 40 547391-0 Fax: +49 40 547391-40 E-mail: info@vitalograph.de

Vitalograph Ltd, Hong Kong/China Unit 2001, Floor 20, Block A New Trade Plaza 6 On Ping Street, Shatin Hong Kong Tel: +852 2117 2678 Fax: +852 2117 2679 E-mail: sales@vitalograph.cn www.vitalograph.cn